

TITLE OF THE INVENTION

SINGLE CHANNEL, RETRACTABLE NEEDLE DIALYZER HEADER CLEANING DEVICE

5

BACKGROUND OF THE INVENTION

[0001] The present invention relates to devices for cleaning dialyzer headers.

10

[0002] Hemodialysis is an extracorporeal therapy whereby blood is pumped out of the body and through a dialyzer, also know as an artificial kidney, and returned back to the body. The dialyzer is composed of two regions: a blood region and a dialysate region, the two regions being separated from one another by a filter-like membrane possibly composed of hollow fibers or flat sheets. The membrane is porous and permits water and small and middle weight molecules to pass across.

20

[0003] The blood that is pumped out of the body is pumped through the blood region of the dialyzer. Dialysate, a fluid that contains the electrolytes the body needs and bicarbonate to aid in acid base balance in the body, is caused to flow through the dialysate region in counter current to the blood flow through the blood region. Toxins in the blood pass across the membrane from the blood region into the dialysate region by diffusion or convection. Electrolytes and bicarbonate pass from the dialysate in the

25

dialysate region across the membrane into the blood region in a similar manner.

[0004] Many dialysis facilities reuse the dialyzers in order to save money. The costs associated with dialyzer reuse include: reuse space, water and electricity, the cost of machines specifically designed to reprocess the dialyzers and reprocessing chemicals, and employee salaries.

[0005] The steps involved in dialyzer reuse vary from clinic to clinic. However, certain steps are universal. After completion of a dialysis treatment, the first step in the reuse process is to rinse any residual blood out of the dialyzer. For this purpose, the dialyzer is connected to a water supply and fluid is flushed through the blood and/or dialysate regions. This process rinses out many of the large particles and blood components left in the dialyzer. After the dialyzer is rinsed the dialyzer is then reprocessed.

[0006] Although many clinics throughout the world manually reprocess the dialyzers, there are currently many machines, such as those marketed by Minntech Corp. under the trade name Renatron, Mesa Medical under the trade name Echo, etc., that are capable of automatically reprocessing dialyzers.

[0007] Automatic reprocessing is similar to manual reprocessing. In automatic reprocessing, the dialyzer is connected to the reprocessing machine by both blood ports (arterial and venous) and both dialysate ports. Water or other cleaning liquid is then flushed through both regions of the dialyzer to further rinse away blood products. This is done in several steps. The cleaning step of dialyzer reprocessing is performed by flushing water mixed with a cleaning agent such as a bleach or peroxyacetic acid, through the dialyzer. This is also performed in other steps including a backflush. The backflush process rinses the water and cleaning agent from the dialysate side through the membrane to the blood region and out of the blood region ports. This backflush process can loosen and remove any blood or blood products that are adhered to the inner wall of the dialyzer fibers.

[0008] Most reused dialyzers are taken out of use, or fail, because the volume of the dialyzer, *i.e.*, the volume of the blood compartment, has dropped below acceptable levels. Any blood products that block the fibers will reduce the volume of the dialyzer. Very rarely does a dialyzer fail due to inadequate results on a leak test.

[0009] The headers of a dialyzer are the part of the dialyzer where the blood enters and leaves the dialyzer. During dialysis, as blood is pumped through the dialyzer,

microclots, fibrin and other biologic products react with the dialyzer and may also react with the extracorporeal circuit consisting of blood lines, the pump and the dialysate compartment. These biologic products are commonly
5 found accumulated in the headers of the dialyzer, many times forming a sheet that can completely block the openings to the fibers and blood region of the dialyzer.

[0010] These biologic products must be removed from the
10 dialyzer in order to obtain adequate blood volume during reuse testing. Currently, flushing water is the most common method used to remove the biologic products from the header of the dialyzer. However, due to the design of the dialyzer header, this is not always effective. Some dialyzers have
15 header caps that can be unscrewed to facilitate cleaning. However, due to concerns of cross contamination, the complexity of properly reassembling such a dialyzer and damage to the dialyzers, removing the header caps is discouraged.

20

[0011] US Patents Nos. 6,050,278 by Arnal et al and 4,375,413 by Geel et al disclose dialyzer cleaning devices having needles for injecting water into the dialyzer head. The device disclosed by Geel et al has a single solid piece
25 for spraying water, which is not capable of rotating or retracting. Arnal et al disclose a needle that may oscillate and retract. Oscillation is effected by a gear

assembly that undergoes reciprocal motion created by a pulsating fluid. Thus, this is a structurally complex device.

5

BRIEF SUMMARY OF THE INVENTION

[0012] The present invention provides a novel device that improves cleaning of dialyzer headers.

10

[0013] Specifically, the invention provides a dialyzer header cleaning device comprising: a housing having two opposed ends and delimiting a passage that extends in a flow direction between the two ends; a connecting element disposed at a first end of the housing for connection to the header; and a flow directing element having a fluid inlet end retained in the passage and a fluid outlet end, the flow directing element having a cleaning position in which the fluid outlet end extends into the header when the first end of the housing is connected to the header, wherein

20

the flow directing element is constructed to rotate about an axis that extends in the flow direction in response to a flow of fluid between the fluid inlet end and the fluid outlet end, and to eject from the fluid outlet end fluid streams that are directed transverse to the flow

25

direction; and/or

the flow directing element is movable parallel to the flow direction between the cleaning position and a back

flush position in response to flow of fluid through the passage from the flow outlet end toward the fluid inlet end to provide a back flush flow path through the passage and around the flow directing element.

5

BRIEF DESCRIPTION OF THE DRAWING

[0014] Figure 1 is an elevational cross-sectional view illustrating a first preferred embodiment of the invention.

[0015] Figure 2 is an elevational, cross-sectional view of one component of the device of Figure 1.

[0016] Figure 3 is a cross-sectional view taken along the line 3-3 of Figure 2.

[0017] Figure 4 is a perspective detail view of a portion of a modified version of a component of the device shown in Figures 1-3.

[0018] Figures 5 and 6 are cross-sectional views of two further embodiments of the component.

[0019] Figure 7 is an elevational, cross-sectional view illustrating a second preferred embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

[0020] The present invention provides a device for cleaning a dialyzer header, which is typically a region delimited by a header cap and one end of the main body of the dialyzer, which contains the dialysate and blood regions. The device according to the invention can be screwed onto the dialyzer header and has a hollow pin, or needle, preferably in a funnel form, that drops into the header and produces a stream or streams of water when connected to a water supply. The streams are preferably directed in a plane parallel to the end surface of the header cap, or can be directed at a small angle to that plane, so as to dislodge biologic products so that they can be easily washed out of the dialyzer. The needle can be made to rotate manually or can be made to spin by the pressure of the incoming water, in order to rinse the entire periphery of the header, or header cap, adjacent its end surface.

[0021] This device will also permit the back flushing of water and biologic products out of the header when fluid is flushed from the other side of the dialyzer. This flow of fluid from the opposite side pushes the needle out of the header, while assuring that the needle remains within the device, so that blood products can be washed out of the dialyzer. As water is flushed from the opposite side, large clots will have the required space to be flushed out of the

dialyzer. To aid in the removal of large clots, propellers may be put on the pin device acting as a blade to macerate the clots as they pass.

5 [0022] Figure 1 shows a preferred embodiment of a header cleaning device 12 according to the invention, together with a portion of a dialyzer header cap 14 and a line 16 provided with a connector 18 for supplying cleaning water or other fluid and receiving backflush liquid.

10

[0023] Device 12 is essentially constituted by a housing having threaded connecting portions at both ends for connection to dialyzer header cap 14 and connector 18, device 12 being formed to have a passage that extends
15 between the ends. As shown, the passage includes a cylindrical main chamber and a tapered section that extends from the chamber to the end provided for connection to header cap 14. A needle 30 having a funnel shape, as described above, is retained via its flared upper end in the
20 tapered section of the passage. Needle 30 is shown not in cross section in Figure 1. The structural details and the operation of needle 30 will be described below.

[0024] Header cap 14 is provided with a coupling
25 arrangement for connection to a dialyzer system, the coupling arrangement including, by way of example, an outer luer flange 22 and an inner luer flange 24. The inner

surface of flange 22 is threaded. Connector 18 is externally threaded.

[0025] Figures 2 and 3 show needle 30 in greater detail, and in particular show the preferred form of outlet openings 42 at the fluid outlet end of needle 30. Outlet openings 42 have the form of nozzles that produce streams or sprays directed tangentially to the outer wall of needle 30. Thus, cleaning liquid is ejected tangentially to the outer wall of needle 30 and produces a reaction force that rotates needle 30 about its longitudinal axis. This, in turn, causes the paths followed by the cleaning liquid streams or sprays to be rotated about that longitudinal axis, assuring impact against the entire periphery of the interior wall of cap 14. One or more openings may be provided, three openings being shown only by way of example. The resulting streams or sprays impact against the periphery of the interior of cap 14, and particularly against the corner between the axial end and the peripheral wall of cap 14 and across the top of the dialyzer, to dislodge blood products.

[0026] As shown in Figure 4 the flared upper end of needle 30 may have grooves or lands 50 that extend at an angle, for example along helical paths, to aid in the rotation of the needle. It is also possible to have a propeller or similar structure that acts as blades to

macerate or break up the clots and blood products as the needle spins.

[0027] Figure 5 illustrates another embodiment of a
5 needle 130 for use in a device according to the invention.
In this embodiment, the tip of needle 130 has one or more
slits 134 that will direct streams perpendicular to the
common longitudinal axis of the device and needle 130 and
thus parallel to end surface of header cap 14. Slit or
10 slits 134 in the tip of needle 130 may extend perpendicular
to the dialyzer header cap end surface, as shown, resulting
in a spray perpendicular to the header in order to dislodge
blood products. The length and angle of the slits are
preferably selected to maximize cleaning capability.

[0028] Figure 6 illustrates a further embodiment of a
needle 230 for use in a device according to the invention.
In this embodiment, the outlet end of needle 230 is open and
is connected via a thin bar 236 to a diverting member 240
20 having a conical diverting surface that forms an angle of
the order of 45° with the longitudinal axis of needle 230.
This arrangement produces a 360° spray in a plane
essentially perpendicular to the longitudinal axis of needle
230 to clean the entire periphery of the interior of cap 14
25 simultaneously. The gap between the outlet end of needle
230 and member 240 may be made relatively small to produce a
high velocity liquid jet.

[0029] Reverting to Figure 1, to clean header cap 14, device 12 may be provided with any one of the needles described above and then is connected to header cap 14 and connector 18 and a flow of cleaning liquid is supplied to device 12 from line 16. This liquid flows downwardly, with respect to the orientation shown in Figure 1, and assures that the needle will be in its cleaning position, shown in solid lines in Figure 1, with the lower extremity, or tip, of the needle extending into the dialyzer header.

[0030] If the device is provided with needle 30, the flow of liquid will cause the needle to spin due to the design of the needle, as described above. The resistance to spin caused by contact between the flared upper edge of needle 30 and the wall of the passage formed in device 12 will be minimized by making the surface area of contact therebetween as small as possible. Spinning of needle 30 may also be aided by providing openings 32 in needle 30 adjacent the fluid inlet of the needle to allow some fluid to pass laterally out of the path enclosed by needle 30 so as to impose a lifting force that reduces or neutralizes the friction force between needle 30 and the wall of the passage formed in device 12, thereby permitting the needle to rotate freely.

[0031] When needle 130 or 230 is used, it will not spin in response to the flow of liquid therethrough. However, particularly if needle 130 is used, according to another embodiment of the invention, which will be described below with reference to Figure 7, the housing containing the needle can be rotated manually to assure thorough cleaning of the interior surfaces of cap 14.

[0032] The fluid that enters the connected dialyzer header travels through the dialyzer and out of the second dialyzer header (not shown) at the opposite end of the dialyzer.

[0033] Once all blood products appear to have been adequately dislodged from the first header, the flow of cleaning liquid is stopped and device 12 is disconnected. Device 12 may then be reconnected to the opposite header cap and the cleaning operation can then be repeated, this time with cleaning liquid flowing in the opposite direction through the dialyzer.

[0034] Blood products that were dislodged during the first cleaning operation but not removed from the dialyzer will be easily flushed out when cleaning liquid is delivered to the header at the opposite end of the dialyzer. Blood products dislodged in the second header by connection of the device thereto, can be removed by again connecting device 12

to the first cap and again causing cleaning liquid to flow through device 12.

[0035] Alternatively, after dislodging blood products from the first header cap, device 12 can remain connected to the first header cap and the water supply line can be connected to the opposite, or second, header cap. The resulting reverse flow, or back flush flow, will force needle 30, 130, or 230 away from the header cap to which it is connected and into the passage in device 12, so that the blood products can be flushed out of the dialyzer header cap, through device 12 and into a sink. When this flow forces the needle upwardly, the flared fluid inlet end thereof is moved to the raised position 30' shown in broken lines in Figure 1. Back flow then occurs through the passage formed in device 12 and through openings 32 in the needle. In addition, gaps or recesses 38 may be provided in the wall of the passage in device 12, at the level of the upper end of the needle when the needle is in the back flow position, to facilitate the back flush flow of liquid and the removal of blood products.

[0036] According to another alternative, two devices according to the invention can be connected to a dialyzer, one at each dialyzer header, and cleaning liquid can be supplied in alternation to each device to quickly remove all blood products.

[0037] In those clinics that perform manual cleaning, one or two devices according to the invention can be connected to the dialyzer header(s) as cleaning and disinfecting agents are flushed through the dialyzer. Similarly, one or two devices can be connected to the dialyzer header(s) and the dialyzer can then be placed on an automatic reprocessing machine and processed.

[0038] A two way, three port stop cock may be placed between the incoming fluid line and the header cleaning device with the third port exposed to air. Such a stop cock is commercially available from Qosina, Inc. of Edgewood, NY. When the stop cock is rotated to circuit the air with the header cleaning device, the water in the header will gravity drain so that the visibility of the header is improved. When rotated to circuit the incoming fluid and the header cleaning device, the incoming fluid forces the needle to rotate within the header and emit a jet transverse to the header. By alternating the stop cock between the incoming fluid line and air, the cleaning of the header and break up of clots will be improved.

[0039] In order to prevent any reflux from the dialyzer out the port open to air, a transducer protector, commercially available from companies such as Nextron Medical of New Jersey, can be placed on the port open to

air. This transducer permits the flow of air, but not fluids or blood products.

[0040] Figure 7, as mentioned earlier herein, shows a second embodiment of the invention composed of a header cleaning device 312 formed to have a passage essentially identically to the passage provided in device 12 of Figure 1. Needle 30 is shown in broken lines to indicate its cleaning position without obscuring other features of device 312. The length of needle 30 is not necessarily shown to scale; it will be dimensioned to assure that when all components are assembled, its tip will be properly positioned inside header cap 14. Each end of device 312 is provided with a quick-connect female coupling element 316, 318. A first adapter 320 is provided with a first quick-connect male coupling portion 322 and male threads 324 connectable to the female threads on the inner surface of flange 22 of header cap 14. A second adapter 330 is provided with a second quick-connected male coupling portion 332 and female threads 334 for connection to connector 18 on line 16 for supplying cleaning water or other fluid is provided with.

[0041] Each female coupling element 316, 318 is provided with a respective latch member 326, 328 for engagement in a groove 340, 342 of a respective coupling portion 322, 332. Each latch member 326, 328 is provided with a compression spring that urges the respective latch member into it

latching position, as shown in Figure 7. Each male coupling portion 322, 332 is provided with a further groove 346, 348, respectively, for receiving a sealing ring (not shown), such as an O ring.

5

[0042] In order to connect device 312 to header 14, adapter 320 is connected to flange 22, latch member 326 is moved laterally, against the force of its associated spring, to an unlatching position and female coupling element 316 is placed around male coupling portion 322. Then, latch member 326 is released so that one portion thereof engages in groove 340. Similarly, adapter 330 is connected to connector 18 and female coupling element 318 is connected to male coupling portion 332 by moving latch member 328 to its unlatching position and inserting coupling portion 332 into the passage provided in coupling element 318, after which latch member 328 is released so that a portion thereof engages in groove 342. With this arrangement, a fluid tight coupling is provided between device 312 and both the interior of header cap 14 and fluid supply line 16, and device 312 can be rotated manually without interfering with these fluid tight connections. Thus, even if needle 30, or needle 130 or 230, does not spin, the entire interior of header cap 14 can be washed by manual rotation of device 312.

[0043] As an alternative to the embodiment shown in Fig. 7, adaptors 320 and 330 can be made integral parts of header cap 14 and line 16, respectively.

5 [0044] A modified version of the device disclosed herein may be usable during dialysis to properly distribute incoming blood into the dialyzer header.

[0045] The foregoing description of the specific
10 embodiments will so fully reveal the general nature of the invention that others can, by applying current knowledge, readily modify and/or adapt for various applications such specific embodiments without undue experimentation and without departing from the generic concept, and, therefore,
15 such adaptations and modifications should and are intended to be comprehended within the meaning and range of equivalents of the disclosed embodiments. It is to be understood that the phraseology or terminology employed herein is for the purpose of description and not of
20 limitation. The means, materials, and steps for carrying out various disclosed functions may take a variety of alternative forms without departing from the invention.

[0046] Thus the expressions "means to..." and "means
25 for...", or any method step language, as may be found in the specification above and/or in the claims below, followed by a functional statement, are intended to define and cover

whatever structural, physical, chemical or electrical
element or structure, or whatever method step, which may now
or in the future exist which carries out the recited
function, whether or not precisely equivalent to the
5 embodiment or embodiments disclosed in the specification
above, i.e., other means or steps for carrying out the same
functions can be used; and it is intended that such
expressions be given their broadest interpretation.

10

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
222